


Pulse Load MELF Resistors for High Frequency Applications



CMA 0204 HF speciality MELF resistors combine the advanced pulse load capability and the suitability for RF applications in a single component. They are the perfect choice in high frequency circuit designs where the parasitic inductance of regular, helical trimmed resistors can not be accepted, but where also pulse energies apply. Typical applications are in the fields of telecommunication equipment and industrial electronics.

FEATURES

- Speciality product for RF applications
- Low-inductance non-helical trimmed product
- Special carbon film technology
- ESD capability: 3 kV, Human Body Model
- Suitable for more than 10 GHz
- Compatible with lead (Pb)-free and lead containing soldering processes
- Lead (Pb)-free and RoHS compliant



APPLICATIONS

- Telecommunication equipment
- Industrial electronics

METRIC SIZE

DIN:	0204
CECC:	RC 3715M

TECHNICAL SPECIFICATION

DESCRIPTION	CMA 0204 HF	
CECC size	RC 3715M	
Resistance range	50 Ω; 47 Ω to 300 Ω	
Resistance tolerance	± 2 %	
Temperature coefficient	approx. - 250 ppm/K	
Operation mode	standard	power
Climatic category (LCT/UCT/days)	55/125/56	55/155/56
Rated dissipation $P_{70}^{1)}$	0.25 W	0.4 W
Operating voltage, U_{max} AC/DC	Limited by P_{70}	
Film temperature	125 °C	155 °C
Max. resistance change at P_{70} for resistance range,	47 Ω to 300 Ω	
$ \Delta R/R $ after:		
1000 h	≤ 1 %	≤ 2 %
8000 h	≤ 2 %	≤ 4 %
225 000 h	t.b.f.	-
Permissible voltage against ambient (insulation):		
1 minute; U_{ins}	300 V	
continuous	75 V	
Failure rate	≤ 1 × 10 ⁻⁹ /h	

Note: These resistors do not feature a limited lifetime when operated within the permissible limits. However, resistance value drift increasing over operating time may result in exceeding a limit acceptable to the specific application, thereby establishing a functional lifetime.

¹⁾ The power dissipation on the resistor generates a temperature rise against the local ambient, depending on the heatflow support of the printed-circuit board (thermal resistance). The rated dissipation applies only if the permitted film temperature is not exceeded. Furthermore, a high level of ambient temperature or of power dissipation may raise the temperature of the solder joint, hence special solder alloys or board materials may be required to maintain the reliability of the assembly.



12NC INFORMATION

- The 12-digit numeric code starts with 2312
- The subsequent 4 digits indicate the resistor type, specification and packaging; see the 12NC table
- The remaining 4 digits indicate the resistance value:
 - The first 3 digits indicate the resistance value.
 - The last digit indicates the resistance decade in accordance with the 12NC Indicating Resistance Decade table.

Last Digit of 12NC Indicating Resistance Decade

RESISTANCE DECADE	LAST DIGIT
10 Ω to 99.9 Ω	9
100 Ω to 999 Ω	1

12NC Example

The 12NC of a CMA 0204 HF resistor, value 50 Ω with ± 1 % tolerance, supplied in blister tape of 3000 units per reel is: 2312 158 25009.

12NC - resistor type and packaging		
DESCRIPTION		ORDERING CODE 2312
		BLISTER TAPE ON REEL
TYPE	TOL.	BL 3000 UNITS
CMA 0204 HF	± 2 % 158 2

PART NUMBER AND PRODUCT DESCRIPTION¹⁾

PART NUMBER²⁾: CMA0204AX1000GB300

C	M	A	0	2	0	4	A	X	1	0	0	0	G	B	3	0	0
MODEL/SIZE CMA0204	SPECIAL CHARACTER A = HF High Frequency	TC X = no indication	VALUE 3 digit value 1 digit multiplier Multiplier 9 = *10 ⁻¹ 0 = *10 ⁰			TOLERANCE G = ± 2 %	PACKAGING ³⁾ B3	SPECIAL up to 2 digits 00 = standard									

PRODUCT DESCRIPTION⁴⁾: CMA 0204 2 % HF BL 100R


CMA	0204	2 %	HF	BL	100R
MODEL	SIZE	TOLERANCE	SUFFIX	PACKAGING ³⁾	RESISTANCE VALUE
CMA	0204	± 2 %	HF = High Frequency	BL	100R = 100 Ω

Note

1. Products can be ordered using either the PRODUCT DESCRIPTION or the 12NC.
2. The PART NUMBER is shown to facilitate the introduction of the unified part numbering system. Currently, this PART NUMBER is applicable in the Americas and in Asia/Pacific only.
3. Please refer to table PACKAGING, see below.
4. For CMA0204 the temperature coefficient is not identified in the PRODUCT DESCRIPTION.

PACKAGING			
TYPE	BLISTER TAPE ON REEL ACC. IEC 60286-3		
	DIAMETER	PIECES/REEL	CODE
CMA 0204 HF	180 mm/7"	3000	B3 = BL

DIMENSIONS



DIMENSIONS - MELF resistor types, mass and relevant physical dimensions						
TYPE	L (mm)	D (mm)	L ₁ min (mm)	D ₁ (mm)	K (mm)	MASS (mg)
CMA 0204 HF	3.6 + 0/- 0.2	1.4 + 0/- 0.1	1.8	D + 0/- 0.15	0.8 ± 0.1	19

¹⁾ Color code marking is applied according to IEC 60062* in four bands. Each color band appears as a single solid line, voids are permissible if at least 2/3 of the band is visible from each radial angle of view. The last color band for tolerance is approximately 50 % wider than the other bands. Interrupted bands left and right of the 3rd full band indicate the special carbon film high frequency type.

TOLERANCE AND RESISTANCE RANGE		
TYPE	TOLERANCE	RESISTANCE VALUE
CMA 0204 HF	± 2 %	50 Ω 47 Ω to 300 Ω ¹⁾

¹⁾ Please select resistance values for ± 2 % tolerance from the E24 series.

**DESCRIPTION**

Production of the CMA 0204 HF speciality MINI-MELF resistor is strictly controlled and follows an extensive set of instructions established for reproducibility. A homogeneous and dense carbon film is deposited on a high grade ceramic body (85 % Al₂O₃). Nickel plated steel termination caps are firmly pressed on the coated rods. A special laser is used to achieve the target value by smoothly cutting a non helical pattern with a resulting low inductivity in the resistive layer without damaging the ceramics. The resistor elements are covered by a protective coating designed for electrical, mechanical and climatic protection. The terminations receive a final pure tin on nickel plating. Four color code rings designate the resistance value and tolerance in accordance with **IEC 60062***.

The result of the determined production is verified by an extensive testing procedure performed on 100 % of the individual resistors. Only accepted products are laid directly into the blister tape in accordance with **IEC 60286-3***.

ASSEMBLY

The resistors are suitable for processing on automatic SMD assembly systems. They are suitable for automatic soldering using wave, reflow or vapour phase as shown in **IEC 61760-1***. Excellent solderability is proven, even after extended storage in excess of 10 years. The encapsulation is resistant to all cleaning solvents commonly used in the electronics industry, including alcohols, esters and aqueous solutions. The resistors are completely lead (Pb)-free, the pure tin plating provides compatibility with lead (Pb)-free soldering processes. The immunity of the plating against tin whisker growth has been proven under extensive testing.

All products comply with the **GADSL**¹⁾ and the **CEPIC-EECA-EICTA**²⁾ list of legal restrictions on hazardous substances. This includes full compliance with the following directives:

- 2000/53/EC End of Vehicle life Directive (ELV) and the Annex II (ELV II)
- 2002/95/EC Restriction of the use of Hazardous Substances Directive (RoHS)
- 2002/96/EC Waste Electrical and Electronic Equipment Directive (WEEE)

¹⁾ Global Automotive Declarable Substance List, see www.gadsl.org

²⁾ CEPIC (European Chemical Industry Council), EECA (European Electronic Component Manufacturers Association), EICTA (European trade organisation representing the information and communications technology and consumer electronics), see www.eicta.org -> issues -> environment policy -> chemicals -> chemicals for electronics

APPROVALS

Where applicable the resistors are tested in accordance with **EN 140401-803** which refers to **EN 60115-1**, **EN 140400** and the variety of environmental test procedures of the **IEC 60068*** series.


Vishay BEYSCHLAG has achieved "**Approval of Manufacturer**" in accordance with **IEC QC 001002-3, clause 2**. The release certificate for "**Technology Approval Schedule**" in accordance with **CECC 240001** based on **IEC QC 001002-3, clause 6** is granted for the Vishay BEYSCHLAG manufacturing process.

Note:


* The quoted IEC standards are also released as EN standards with the same number and identical contents.




FUNCTIONAL PERFORMANCE



Derating - Standard Operation



1.2/50 Pulse Pulse load rating in accordance with IEC 60115-1, 4.27; 1,2 μs/50 μs; 5 pulses at 12 s intervals; for permissible resistance change 0.5 %



RF - Behaviour



REVISION HISTORY

Compared to the prior revision of this datasheet, CMA HF 030331, the following changes have been applied:

- Transfer into Vishay format for publication on the internet
- Introduction of a standardized part numbering system
- Emphasis on the clean balance of materials and on the compliance with various EU directives
- Introduction of information on electrostatic discharge (ESD) capability
- No other change of technical contents
- No product change



Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.